







DBD250

Terminal Type - DBD250, Panel + Chanel Mounted distribution block, nominal voltage: 1000 V AC / 1500 V DC, nominal current: 250 A, Rated cross-section - IC-120 mm², OG-2x35 mm², 4x10 mm² & 5x16 mm², connection method: Screw connection, number of connections: 12, cross-section: IC - 1X 35-120 mm², OG-2X 2.5-35 mm², 4X2.5-10 mm², 5X2.5-16 mm², mounting type: TS35/15, TS35/7.5, or Panel Mounted

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Marker For Terminal Blocks		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	

Marker carriers		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	