


















KABTM3

Terminal Type - KABTM3 , Feed Through Terminal Block, nominal voltage: 800 V(Tested at 1100 V), nominal current: 24 A, connection method: Bolt Connection - Screw and Nut driver operated, number of connections: 2, Rated cross section: 2.5 mm², cross section: 0.5 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15, TS 32

Product Accessories

Cover Profile		
PCC3K	Height : 17.50 mm Width : 50.00 mm Thickness : 1.50 mm	
PCCM17K	Height : 13.20 mm Width : 17.00 mm Thickness : 1.25 mm	
PCCM25.5K	Height : 13.20 mm Width : 25.50 mm Thickness : 1.25 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPS4	Height : 32.00 mm Width : 1.50 mm Length : 50.00 mm	
Insertion Bridge		
KSL3-2W	Height : 25.50 mm Width : 3.50 mm Pitch : 8.50 mm Length : 15.00 mm	
KSL3-10W	Height : 25.50 mm Width : 3.50 mm Pitch : 8.50 mm Length : 83.00 mm	

Insertion Bridge		
KSL3-3W	Height : 25.50 mm Width : 3.50 mm Pitch : 8.50 mm Length : 23.50 mm	
KSL3-4W	Height : 25.50 mm Width : 3.50 mm Pitch : 8.50 mm Length : 32.00 mm	
KSL3-5W	Height : 25.50 mm Width : 3.50 mm Pitch : 8.50 mm Length : 40.50 mm	
Marker For Terminal Blocks		
LABEL KN6.5	Height : 2.42 mm Width : 6.70 mm Length : 8.50 mm	
Partition Plate		
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	