












KLTD4



Terminal Type - KLTD4, Test Disconnect terminal block, nominal voltage: 1000 V (Tested At - 1100 V) , nominal current: 41 A, connection method: Bolt Connection, number of connections: 2, Rated cross section: 6 mm², cross section: 0.5 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32

Product Accessories

Cover Profile		
PCCM24	Height : 21.00 mm Width : 75.50 mm Thickness : 1.00 mm	
PCCM36	Height : 21.00 mm Width : 75.50 mm Thickness : 1.25 mm	
PCD3	Height : 26.20 mm Width : 73.00 mm Thickness : 1.50 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPLD	Height : 49.30 mm Width : 1.50 mm Length : 74.10 mm	
Fixed Bridge		
CCLAKLTDM4-10W	Height : 24.00 mm Width : 6.00 mm Pitch : 12.00 mm Length : 117.00 mm	
CCLAKLTDM4-2W	Height : 24.00 mm Width : 6.00 mm Pitch : 12.00 mm Length : 21.00 mm	

Fixed Bridge		
CCLAKLTDM4-3W	Height : 24.00 mm Width : 6.00 mm Pitch : 12.00 mm Length : 33.00 mm	
CCLAKLTDM4-4W	Height : 24.00 mm Width : 6.00 mm Pitch : 12.00 mm Length : 45.00 mm	
CCLAKLTDM4-5W	Height : 24.00 mm Width : 6.00 mm Pitch : 12.00 mm Length : 57.00 mm	
Insertion Bridge		
KDSL4-10W	Width : 115.50 mm Pitch : 12.00 mm Length : 27.00 mm	
KDSL4-3W	Width : 31.50 mm Pitch : 12.00 mm Length : 27.00 mm	
KDSL4-4W	Width : 43.50 mm Pitch : 12.00 mm Length : 27.00 mm	
KDSL4-5W	Width : 55.50 mm Pitch : 12.00 mm Length : 27.00 mm	
KDSL4-6W	Width : 67.50 mm Pitch : 12.00 mm Length : 27.00 mm	
KDSL4-2W	Width : 19.50 mm Pitch : 12.00 mm Length : 27.00 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	

