












KUPTD6S

Terminal Type - KUPTD6S , Test Disconnect Terminal Block , nominal voltage: 630 V, nominal current: 24 A, Rated cross-section: 6.0 mm², connection method: Screw connection with spring support, number of connections: 2, Rated Cross-section : 6 mm² , cross section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15, TS32

Product Accessories

| DIN Rail Perforated | | |
|-------------------------------|--|---|
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| CHS | Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm |  |
| DIN Rail, Unperforated | | |
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| End Cap | | |
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
| End Clamp | | |
| SCUP | Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm |  |
| SCEC35 | Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm |  |
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |

| End Clamp | | |
|--------------|--|---|
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| DCKN | Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm |  |
| DCKN10 | Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCKN | Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |
| End Cover | | |
| KPPDS | Height : 57.40 mm Width : 2.00 mm Length : 72.50 mm |  |
| Fixed Bridge | | |
| CCLAK6-2W | Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 14.35 mm |  |
| CCLAK6-10W | Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 78.75 mm |  |
| CCLAK6-3W | Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 22.40 mm |  |
| CCLAK6-4W | Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 30.45 mm |  |
| CCLAK6-5W | Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 38.50 mm |  |

| Marker For Terminal Blocks | | |
|----------------------------|---|---|
| LABEL KN8 | Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm |  |

| Marker carriers | | |
|-----------------|--|--|
| SCUDDMLH | Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm |  |
| SCUNMLH | Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm |  |
| DCKNMLH | Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCKNMLH | Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm |  |

