

## OAT6


Terminal Type - OAT6 , Feed through terminal block with secured hinged cover, nominal voltage: 1000 V, nominal current: 57 A, Rated Cross-Section : 10 mm<sup>2</sup>, connection method: Bolt connection, number of connections: 2, cross section: 1.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, AWG: 20 - 10 , mounting type: TS 35/7.5, TS 35/15 , TS 32


### Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

<b>End Clamp</b>		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
OEP 6	Height : 39.50 mm Width : 1.50 mm Length : 43.50 mm	
<b>Insertion Bridge</b>		
OSL6-10W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 107.00 mm	
OSL6-2W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 19.00 mm	

Insertion Bridge		
OSL6-3W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 30.00 mm	
OSL6-4W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 41.00 mm	
OSL6-5W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 52.00 mm	
OSL6R-10W	Height : 25.70 mm Pitch : 11.00 mm Length : 107.00 mm	
OSL6R-2W	Height : 25.70 mm Pitch : 11.00 mm Length : 19.00 mm	
OSL6R-3W	Height : 25.70 mm Pitch : 11.00 mm Length : 30.00 mm	
OSL6R-4W	Height : 25.70 mm Pitch : 11.00 mm Length : 41.00 mm	
OSL6R-5W	Height : 25.70 mm Pitch : 11.00 mm Length : 52.00 mm	
OSL6R-6W	Height : 25.70 mm Pitch : 11.00 mm Length : 63.00 mm	

Marker For Terminal Blocks		
LABEL KN 9	Height : 2.00 mm Width : 9.00 mm Length : 6.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	

Marker carriers		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	