


KDPT35

Terminal Type - KDPT35, Test - Disconnect terminal block, nominal voltage: 1500 V, nominal current: 30 A, Rated Cross Section : 6 mm² connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 32



Approvals



General Information

Product Name	KDPT35
Connection Method	Screw Connection
Rating	1500 V / 30 A / 6.00 mm ² / 1.2 Nm
HSN Number	85389000
Standard Packing Qty (in No)	10
Country Of Origin	INDIA
Screw thread	M3.5

Dimensions & Weight

Width	15 mm	0.59 inch
Length	138 mm	5.43 inch
Height	79 mm	3.11 inch
Weight of std. Packing Unit	0.82 Kg	




Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khaki

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Cover		
KDPT35EP	Height : 65.00 mm Width : 2.50 mm Length : 138.00 mm	
Marker For Terminal Blocks		
LABEL KN10	Height : 2.89 mm Width : 10.00 mm Length : 8.50 mm	
Isolating Plug		
KDPTDP	Height : 46.10 mm Thickness : 10.00 mm Length : 43.45 mm	