



KUDDF4AD48V

Terminal Type - KUDDF4AD48V, Fuse terminal block with LED of 48 V AC/ V DC for fuse failure indication, nominal voltage: 630 V, nominal current: UT-6.3 A / LT 28 A, suitable size of cartridge fuse : 5X20 mm and 5x25 mm, Rated cross-section – 2.5 mm², connection method: Screw connection, number of connections: 4, cross-section: 0.5 mm² - 4 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	KUDDF4AD48V
Connection Method	Screw Connection
Rating	630 V / UT-6.3 A , LT-28 A / 2.5 mm ² / 0.5 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	8 mm	0.31 inch
Length	74 mm	2.91 inch
Height	62 mm	2.44 inch
Weight of std. Packing Unit	1.18 Kg	






Material Data








Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khaki

Rated Conductor Size




Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Insertion Bridge		
UFSL-10W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 79.50 mm	
UFSL-3W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 22.10 mm	
UFSL-4W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 30.30 mm	
UFSL-5W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 38.50 mm	
UFSL-2W	Height : 22.50 mm Width : 2.60 mm Pitch : 8.20 mm Length : 13.90 mm	
Marker For Terminal Blocks		
LABEL KN5.5	Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm	
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	

Partition Plate		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	