


KUPTD6S

Terminal Type - KUPTD6S, Test Disconnect Terminal Block , nominal voltage: 630 V, nominal current: 24 A, Rated cross-section: 6.0 mm², connection method: Screw connection with spring support, number of connections: 2, Rated Cross-section : 6 mm², cross section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15, TS32



Approvals



General Information

Product Name	KUPTD6S
Connection Method	Screw Connection with spring support
Rating	630 V / 24 A / 6 mm ² / 1.5 Nm
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	72.5 mm	2.85 inch
Height	72.39 mm	2.85 inch
Weight of std. Packing Unit	1.79 Kg	








Material Data






Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khaki

Rated Conductor Size



Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPPDS	Height : 57.40 mm Width : 2.00 mm Length : 72.50 mm	
Fixed Bridge		
CCLAK6-2W	Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 14.35 mm	
CCLAK6-10W	Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 78.75 mm	
CCLAK6-3W	Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 22.40 mm	
CCLAK6-4W	Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 30.45 mm	
CCLAK6-5W	Height : 28.10 mm Width : 6.30 mm Pitch : 8.05 mm Length : 38.50 mm	

Marker For Terminal Blocks		
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	