


OAT6DTS

Terminal Type - OAT6DTS, Test Disconnect Terminal Block, nominal voltage: 1000 V (Tested at 1100 V), nominal current: 41 A, connection method: Bolt connection, number of connections: 2, cross-section: 0.5 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	OAT6DTS
Connection Method	Bolt Connection
Rating	1000 V / 41 A / 6 mm ² / 1.5 Nm
HSN Number	8904476704177
Standard Packing Qty (in No)	40
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	11 mm	0.43 inch
Length	83 mm	3.27 inch
Height	51 mm	2.01 inch
Weight of std. Packing Unit	1.6 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²


Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²


Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Product Accessories

Cover Profile

PCPDBF-5	Height : 14.10 mm Thickness : 1.50 mm Length : 113.00 mm	
----------	--	---


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	



DIN Rail, Unperforated









CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	






End Cap



CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp




SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
OEP6DTS	Height : 41.60 mm Width : 2.00 mm Length : 83.00 mm	
Insertion Bridge		
OSL6R-10W	Height : 25.70 mm Pitch : 11.00 mm Length : 107.00 mm	
OSL6R-2W	Height : 25.70 mm Pitch : 11.00 mm Length : 19.00 mm	
OSL6R-3W	Height : 25.70 mm Pitch : 11.00 mm Length : 30.00 mm	
OSL6R-4W	Height : 25.70 mm Pitch : 11.00 mm Length : 41.00 mm	

Insertion Bridge		
OSL6R-5W	Height : 25.70 mm Pitch : 11.00 mm Length : 52.00 mm	
OSL6-10W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 107.00 mm	
OSL6-2W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 19.00 mm	
OSL6-3W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 30.00 mm	
OSL6-4W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 41.00 mm	
OSL6-5W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 52.00 mm	
OSL6R-6W	Height : 25.70 mm Pitch : 11.00 mm Length : 63.00 mm	
Marker For Terminal Blocks		
LABEL KN 9	Height : 2.00 mm Width : 9.00 mm Length : 6.00 mm	
Partition Plate		
DBF-5	Height : 54.00 mm Width : 3.00 mm Length : 112.00 mm	
Switching Jumper		
OSLD6-2W	Height : 23.70 mm Width : 20.00 mm Pitch : 11.00 mm	

Switching Jumper			
OSLD6-3W	Height : 23.70 mm Width : 31.00 mm Pitch : 11.00 mm		
OSLD6-4W	Height : 23.70 mm Width : 42.00 mm Pitch : 11.00 mm		

Test Adapter / Test Socket			
OAT6DTSTP-Y	Height : 41.00 mm Width : 6.00 mm		
OAT6DTSTP-B	Height : 41.70 mm Width : 6.00 mm		
OAT6DTSTP-BL	Height : 41.70 mm Width : 6.00 mm		
OAT6DTSTP-G	Height : 41.70 mm Width : 6.00 mm		
OAT6DTSTP-GR	Height : 41.70 mm Width : 6.00 mm		
OAT6DTSTP-R	Height : 41.70 mm Width : 6.00 mm		

Marker carriers			
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm		
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm		

Marker carriers		
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	
Switching Lock		
OAT6DTSLP	Height : 40.80 mm Thickness : 7.90 mm Length : 21.05 mm	

