


SQTM2.5

Terminal Type: SQTM2.5, Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A, Rated cross section: 2.5 mm², connection method: Spring Cage Connection, number of connections: 2, cross-section: 0.08 mm² – 4 mm², mounting type: TS15



Approvals



General Information

Product Name	SQTM2.5
Connection Method	Spring Cage Connection
Rating	800 V / 24 A / 2.5 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	5 mm	0.2 inch
Length	33.3 mm	1.31 inch
Height	30 mm	1.18 inch
Weight of std. Packing Unit	0.48 Kg	


Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Product Accessories

DIN Rail Perforated		
CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
End Cover		
SQTMCP	Height : 22.20 mm Width : 4.00 mm Length : 32.00 mm	
Marker For Terminal Blocks		
KNLVR5	Height : 2.36 mm Width : 5.00 mm Length : 5.00 mm	
Plug-in Bridge/Jumper		
SLFP2.5-2W	Height : 20.60 mm Width : 6.40 mm Pitch : 4.95 mm Length : 8.80 mm	

