


SQTM2.5P4

Terminal Type -SQTM2.5P4, Mini and Micro Terminal block, nominal voltage: 800 V, nominal current: 24 A, connection method: Spring Cage Connection, number of connections: 4 (1 Input & 3 Output), Rated cross section: 2.5 mm², cross-section: 0.08 mm² – 4 mm², mounting type: TS 15



Approvals



General Information

Product Name	SQTM2.5P4
Connection Method	Spring Cage Connection
Rating	800 V / 24 A / 2.5 mm ²
HSN Number	85389000
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	-

Dimensions & Weight

Width	10 mm	0.39 inch
Length	33.3 mm	1.31 inch
Height	30 mm	1.18 inch
Weight of std. Packing Unit	0.47 Kg	


Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Product Accessories

DIN Rail Perforated		
CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
End Cover		
SQTMCP	Height : 22.20 mm Width : 4.00 mm Length : 32.00 mm	
Marker For Terminal Blocks		
KNLVR5	Height : 2.36 mm Width : 5.00 mm Length : 5.00 mm	
Plug-in Bridge/Jumper		
SLFP2.5-2W	Height : 20.60 mm Width : 6.40 mm Pitch : 4.95 mm Length : 8.80 mm	

