



DBK3

Terminal Type - DBK3 , Distribution Block, nominal voltage: 800 V, nominal current: 57 A, connection method: Screw connection, Rated Cross section - IC - 10 mm² , OG - 10 mm² , number of connections: 6, cross section: 2.5 mm² - 16 mm² , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	DBK3
Connection Method	Screw Connection
Rating	800 V/57 A/IC - 10 mm ² , OG - 10 mm ² /1.2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	25
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	31.5 mm	1.24 inch
Length	42.5 mm	1.67 inch
Height	46.4 mm	1.83 inch
Weight of std. Packing Unit	1.49 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	2.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	2.5 mm ²
Conductor cross section solid max	16 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	57 A
Nominal cross section	IC - 10 mm ² , OG - 10 mm ²
Short-time current	1.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

