


DST4

Terminal Type - DST4 , Feed-through terminal block, nominal voltage: 800 V, nominal current: 32 A, Rated cross-section – 4 mm², connection method: Spring Cage connection, number of connections: 2, cross section: 0.5 mm² - 4 mm², AWG: 20 - 12, mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	DST4
Connection Method	Spring Cage Connection
Rating	800 V/32 A/4 mm ² /NAP Nm
HSN Number	8904476702333
Standard Packing Qty(in No)	100
Country Of Origin	INDIA
Screw thread	NAP

Dimensions & Weight

Width	6 mm	0.24 inch
Length	59 mm	2.32 inch
Height	33.5 mm	1.32 inch
Weight of std. Packing Unit	0.99 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	32 A
Nominal cross section	4 mm ²
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	500 V
ATEX Nominal Current I_n	24 A
ATEX Cross Sec. Flexible Max.	4 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	20 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	12 AWG

Ratings - UL

UL Standard	
B - UL Nominal Voltage U_N	V
B - UL Nominal Current I_N	A
B - UL Wire Min	AWG
B - UL Wire Max	AWG