


KDPT35

Terminal Type - KDPT35, Test - Disconnect terminal block, nominal voltage: 1500 V, nominal current: 30 A, Rated Cross Section : 6 mm² connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 32



Approvals



General Information

Product Name	KDPT35
Connection Method	Screw Connection
Rating	1500 V/30 A/6.00 mm ² /1.2 Nm
HSN Number	8904476705099
Standard Packing Qty(in No)	10
Country Of Origin	INDIA
Screw thread	M3.5

Dimensions & Weight

Width	15 mm	0.59 inch
Length	138 mm	5.43 inch
Height	79 mm	3.11 inch
Weight of std. Packing Unit	0.82 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1500 V
Nominal Current I_n	30 A
Nominal cross section	6.00 mm ²
Short-time current	0.72 kA
Rated surge voltage	15 kV
Degree of pollution	3

