



KLTD4-2WAY

Terminal Type - KLTD4-2WAY , Test Disconnecting terminal block, nominal voltage: 800 V, nominal current: 41 A, connection method: Stud type connection, number of connections: 4, Rated Cross Section: 2x6 mm², cross section: 0.5 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	KLTD4-2WAY
Connection Method	Bolt Connection
Rating	800 V/41 A/2x6 mm ² /1.2 Nm
HSN Number	NAV
Standard Packing Qty(in No)	25
Country Of Origin	INDIA
Screw thread	M4

Dimensions & Weight

Width	24 mm	0.94 inch
Length	74 mm	2.91 inch
Height	49.5 mm	1.95 inch
Weight of std. Packing Unit	1.02 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	41 A
Nominal cross section	2x6 mm ²
Short-time current	0.72 kA
Rated surge voltage	6 kV
Degree of pollution	3

