


KUPTD6S

Terminal Type - KUPTD6S, Test Disconnect Terminal Block , nominal voltage: 630 V, nominal current: 24 A, Rated cross-section: 6.0 mm², connection method: Screw connection with spring support, number of connections: 2, Rated Cross-section : 6 mm², cross section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15, TS32



Approvals



General Information

Product Name	KUPTD6S
Connection Method	Screw Connection with spring support
Rating	630 V/24 A/6 mm ² /1.5 Nm
HSN Number	8904476704528
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	72.5 mm	2.85 inch
Height	72.39 mm	2.85 inch
Weight of std. Packing Unit	1.79 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	630 V
Nominal Current I_n	24 A
Nominal cross section	6 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

