


PAT100

Terminal Type - PAT100, High current connectors, nominal voltage: 1000 V, nominal current: 100 A, Rated cross-section: 25 mm², connection method: Bolt connection, number of connections: 2, cross-section: 10 mm² - 25 mm², mounting type: Panel mounted / Surface mounted



Approvals



General Information

Product Name	PAT100
Connection Method	Bolt Connection
Rating	1000 V/100 A/25 mm ² /3 Nm
HSN Number	8904476703903
Standard Packing Qty(in No)	25
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	41 mm	1.61 inch
Length	50 mm	1.97 inch
Height	40 mm	1.57 inch
Weight of std. Packing Unit	0.94 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khaki ,

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	25 mm ²
Conductor cross section solid min	10 mm ²
Conductor cross section solid max	25 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	100 A
Nominal cross section	25 mm ²
Short-time current	3 kA
Rated surge voltage	8 kV
Degree of pollution	3

