


## SQ4-2X2

Terminal Type - SQ4-2X2 , Multi Conductor feed through terminal block , connection method: Spring Cage Connection , Nominal Voltage : 1000 V , Nominal Current : 32 A , Rated cross section: 4.0 mm<sup>2</sup>, Number of connections: 4, cross section: 0.08 mm<sup>2</sup> - 6 mm<sup>2</sup> , AWG : 24-10 , mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	SQ4-2X2
Connection Method	Spring Cage Connection
Rating	1000 V/32 A/4 mm <sup>2</sup> /NAP Nm
HSN Number	8904476701121
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

### Dimensions & Weight

Width	6 mm	0.24 inch
Length	90.2 mm	3.55 inch
Height	36 mm	1.42 inch
Weight of std. Packing Unit	1.53 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	6 mm <sup>2</sup>

### Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	32 A
Nominal cross section	4 mm <sup>2</sup>
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

### Ratings - ATEX

ATEX Standard	EN 60049-7
ATEX Nominal Voltage $U_n$	630 V
ATEX Nominal Current $I_n$	28 A
ATEX Cross Sec. Flexible Max.	4 mm <sup>2</sup>

### Ratings - CSA

CSA Standard	
B - CSA Nominal Voltage $U_N$	V
B - CSA Nominal Current $I_N$	A
B - CSA Wire Min	AWG
B - CSA Wire Max	AWG

### Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage $U_N$	600 V
B - UL Nominal Current $I_N$	30 A
B - UL Wire Min	24 AWG
B - UL Wire Max	10 AWG